Specifications Sheet

The Ventis® MX4 is a four-gas monitor with the portability and size of a single-gas monitor. Eliminate the need for extra monitors and transition seamlessly from personal monitoring to confined space entry with the Ventis® Slide-on Pump—ideal for operators who wear their gas monitors primarily for personal protection but occasionally require a pump for confined space entries.

- Detect up to four gases with a wide range of sensor options
- Select alarm set points, set latch alarms, disable instrument shutdown while in alarm, and more
- Save time and reduce human error with maintenance and usage data available from iNet Control software
- Available with or without an integral pump, or with the Ventis Slide-on Pump for ultimate flexibility
- Non-pumped instruments compatible with 12-hour, 18-hour, or 20-hour batteries

The Ventis® Slide-on Pump

The Ventis® Slide-on Pump is ideally suited for operators who wear their gas monitors primarily for personal protection but occasionally require a pump for confined space entries. Available in black or safety orange and powered by its own battery, the slide-on pump is compatible with the Ventis MX4 and Ventis® Pro5 Multi-Gas Monitor.

- **Convenient Sampling –** Sample draw distance of up to 50 feet provides convenient sampling in a wide range of applications
- **Easy to Attach –** No tools are required to attach or remove the Ventis Slide-on Pump to or from the monitor
- **Uses Same Batterys and Chargers as Ventis –** Monitor and pump each use the same batterys, and can easily be exchanged between instruments
- **Flexible Battery Options –** Three available battery options make this pump extremely flexible in the field

SPECIFICATIONS*

WARRANTY
The following components are warranted for four (4) years from the device's date of manufacture: monitor, pump, and CO/H_2S/O_2/LEL sensors. All other components are warranted for two (2) years from the device's date of manufacture.**

CASE MATERIAL
Polycarbonate with protective rubber overmold

DIMENSIONS
103 x 58 x 30 mm (4.1 x 2.3 x 1.2 in) without pump, lithium-ion battery version
172 x 67 x 66 mm (6.8 x 2.6 x 2.6 in) with pump, lithium-ion battery version

WEIGHT
182 g (6.4 oz) without Pump, lithium-ion battery version
380 g (13.4 oz) with Pump, lithium-ion battery version

POWER SOURCE/RUN TIME
Rechargeable slim extended lithium-ion battery
(18 hours typical @ 20 °C) without Pump
Rechargeable lithium-ion battery
(12 hours typical @ 20 °C) without Pump
Rechargeable extended-range lithium-ion battery
(20 hours typical @ 20 °C) without Pump
(12 hours typical @ 20 °C) with Pump
Replaceable AAA alkaline battery
(8 hours typical @ 20 °C) without Pump
(4 hours typical @ 20 °C) with Pump

ALARMS
Ultra-bright LEDs, loud audible alarm (95 dB at 30 cm) and vibrating alarm

DISPLAY/READOUT
Backlit liquid crystal display (LCD)

TEMPERATURE RANGE
-20 °C to 50 °C (-4 °F to 122 °F) ***

HUMIDITY RANGE
15% to 95% Non-condensing (continuous)

SENSORS
Combustible gases/methane – Catalytic Bead
O_2, CO, CO/H_2 low, H_2S, NO_2, SO_2 – Electrochemical

MEASURING RANGES

Combustible Gases:	0-100% LEL in 1% increments
Methane (CH_4):	0-5% of vol in 0.01% increments
Oxygen (O_2):	0-30% of vol in 0.1% increments
Carbon Monoxide (CO/H_2 low):	0-1,000 ppm in 1 ppm increments
Carbon Monoxide (CO):	0-1,000 ppm in 1 ppm increments
Hydrogen Sulfide (H_2S):	0-500 ppm in 0.1 ppm increments
Nitrogen Dioxide (NO_2):	0-150 ppm in 0.1 ppm increments
Sulfur Dioxide (SO_2):	0-150 ppm in 0.1 ppm increments

CERTIFICATIONS
INGRESS PROTECTION IP66/67

ANZEx:	Ex ia s Zone 0 I/IIC T4
ATEX:	Ex ia IIC T4 Ga and Ex ia I Ma; Equipment Group and Category II 1G/I M1
China CMC:	Metrology approval
China CPC:	CPA 2017-C103
China Ex:	Ex ia IIC T4 Ga; Ex ia d I Mb
China KA:	Approved for Underground Mines with CO, H_2S, O_2 and CH_4
China MA:	Approved for Underground Mines with CO, H_2S, O_2 and CH_4 (Note: Diffusion 17144453 pack only)
CSA:	Cl I, Div 1, G A-D, T4; Ex d ia IIC T4
EAC:	PB Ex d ia I X/1Ex d ia IIC T4 X
IECEx:	Ex ia IIC T4 Ga
INMETRO:	Ex ia IIC T4 Ga
KC:	Ex d ia IIC T4
KIMM:	Ex d ia IIC T4
MED:	Portable Multi-Gas Detector; Category 2 (MED 96/98/EC; MED 2012/32/EU Marine Directive) Li-ion
MSHA:	30 CFR Part 22; Permissible for underground mines; Li-ion
PA-DEP:	BFE 46-12 Permissible for PA Bituminous Underground Mines; Charger/docking station accessories; Category 1
SANS:	SANS 1515-1; Type A; Ex ia I/IIC T4; Li-ion
TIIS:	Ex ia IIC T4 X
UL:	Cl I, Div 1, Groups A-D, T4; Zone 0, AEx ia IIC T4; Cl II, Gr F-G (Carbonaceous and Grain dust)

SUPPLIED WITH MONITOR
Calibration Cup (without pump), Sample Tubing (with pump), Reference Guide

LANGUAGE
English (1), French (2), Spanish (3), German (4), Italian (5), Dutch (6), Portuguese (7), Russian (9), Polish (A), Czech (B), Chinese (C), Danish (D), Norwegian (E), Finnish (F), Swedish (G), Japanese (J)

* These specifications are based on performance averages and may vary by instrument.

**The 4-year warranty is strictly limited to the enumerated components in devices manufactured after December 31, 2019. Warranted components in devices manufactured before January 1st, 2020 are warranted for two (2) years from the device's date of manufacture.

*** Operating temperatures above 50 °C (122 °F) may cause reduced instrument accuracy. Operating temperatures below -20 °C (-4 °F) may cause reduced instrument accuracy and affect display and alarm performance. See Product Manual for details.